2007 Highlander Features

| | Hybrid | Hybrid Limited | 4WD V6 | 4WD V (7-Seat |
|--|--------|-------------------|-----------|------------------|
| INTERIOR | | | | |
| AM/FM Cassette/CD Player, 6-Speakers, Diversity Antenna | ٠ | - | ٠ | ٠ |
| JBL Audio, AM/FM Cassette/CD Changer, 8-Speakers, Diversity Antenna, | | | | |
| Steering Wheel Audio Controls | _ | • | - | - |
| Air Conditioning, Cabin Air Filter, Rear Seat Heater Ducts | • | - | • | • |
| Air Conditioning w/Automatic Climate Control, Rear Auxiliary Heater, Cabin Air Filter, Rear Seat Heater Ducts | _ | • | _ | _ |
| Fabric Seat Material | • | _ | • | • |
| Leather Seat Surfaces | _ | • | _ | _ |
| Front Captain Seats w/Foldable Armrests | • | • | • | |
| Driver & Front Passenger Seat Recline, Headrest Vertical Adjustments | • | _ | • | • |
| Power Heated 10-Way Adjustable Driver Seat & Power Heated 4-Way Adjustable | | | | |
| Front Passenger Seat | - | • | - | - |
| 60/40 Split Rear Bench Seat w/Fold-Down Seat Back, Recline, Slide, | | | | |
| Headrests-Vertical Adjustments, Fold-Down Centre Armrest | • | - | • | - |
| 60/40 Split 2nd Row Bench Seat w/Fold-Down Seat Back, Recline, Slide, | | | | |
| Headrests-Vertical Adjustments, Fold-Down Centre Armrest | - | • | - | • |
| 3rd Row Bench Seat w/Fold-Down Seat Back, Headrest-Vertical Adjustment | - | • | - | • |
| Power Door Locks | • | • | • | • |
| Power Windows w/Driver Side Auto/Up Down | • | • | ٠ | • |
| Water Temperature Gauge, Dual Trip Odometer | • | • | • | • |
| Tachometer | _ | - | • | • |
| Multi-Information Display, Power Meter | ٠ | • | - | - |
| Outside Temperature Gauge | - | • | - | - |
| Dual Vanity Mirrors | • | - | • | • |
| Dual Illuminated Vanity Mirrors, Electrochromic Rear View Mirror w/Digital Compass | - | • | - | - |
| 4-Spoke Tilt Steering Wheel Leather-Wrapped Steering Wheel, Shift Knob | • | • | • | • |
| Simulated Leather Door Trim | _ | • | - | - |
| Metallic Dash Accents | _ | • | • | - |
| Carpeting, Carpet Floor Mats | • | • | • | • |
| Tonneau Cover | - | | - | |
| CONVENIENCE | | | | |
| Cruise Control | • | • | • | • |
| Digital Clock | • | • | • | • |
| Front & Rear Cup Holders | • | • | • | • |
| Driver's Coin Case Compartment | • | • | • | • |
| Coat Hooks | • | • | • | • |
| Front Centre Console Box | • | • | • | • |
| Driver & Front Passenger Seat Back Pockets | • | • | • | • |
| Door Map Pockets | • | • | • | • |
| Cargo Area Tie-Down Rings | • | • | • | • |
| Overhead Sunglass Storage | ٠ | ٠ | ٠ | • |
| Integrated Garage Door Opener | _ | • | _ | _ |
| Map Lamps | _ | ٠ | ٠ | • |
| Front & Rear Area Lamps | ٠ | • | _ | _ |
| Glove Box Interior Lamp, Cargo Lamp, Door Courtesy Lamps | ٠ | • | ٠ | • |
| Accessory Power Outlet | ٠ | ٠ | ٠ | • |
| Keyless Entry | ٠ | ٠ | ٠ | • |
| Illuminated Entry, Illuminated Ignition Key | ٠ | ٠ | ٠ | • |
| ● - Standard O - Ontional Not Available | | | | |

 $[\]circ =$ Optional - =Not Available • = Standard

| 64777V | Hybrid | Hybrid Limited | 4WD V6 | 4WD V (7-Seat |
|---|--------|-------------------|-----------|------------------|
| SAFETY | | | | |
| Dual-Stage Driver & Front Passenger Airbag Supplemental Restraint System (SRS)* | • | • | • | • |
| Front Passenger Airbag Occupancy Classification Indicator | • | • | • | • |
| Front Seat-Mounted Side Airbag (SRS)* Roll-Sensing Front & Rear Head/Side Curtain Airbags (SRS)* | • | • | • | • |
| Front Seatbelt Pre-Tensioners & Force Limiters | • | • | • | • |
| VII-Position 3-Point Lap & Shoulder Belts | • | • | • | • |
| Adjustable "B" Pillar Shoulder Belt Anchors | • | • | • | |
| Anchor Points for Child Restraint Seats | • | • | • | |
| Thild Protector Rear Door Locks | • | • | • | - |
| Engine Immobilizer | • | • | • | |
| /ehicle Anti-Theft System | - | • | - | _ |
| Front Tow Hook | • | | • | |
| Assist Grips | • | • | • | |
| Remote Fuel Lid Release | • | • | • | |
| Fire Pressure Monitoring System | _ | _ | • | |
| Door Ajar, Low Washer Fluid, Low Fuel, Warning Indicators | • | • | | |
| Driver & Front Passenger Seatbelt Warning Indicators | | | • | |
| EXTERIOR | • | • | • | |
| 6″ Aluminum Alloy Wheels, Wheel Locks | | | | |
| 17" Aluminum Alloy Wheels, Wheel Locks | | _ | • | • |
| lectric Rear Window Defroster w/Timer | • | • | - | - |
| Privacy Glass | • | • | • | - |
| Coloured Bumpers, Door Handles, Mirrors, Grille, Bodyside Mouldings, | • | • | • | - |
| Splash Guards, Black Roof Rack | • | • | • | |
| imited Badging, Power Moonroof, Coloured Rear Spoiler | • | • | • | - |
| Jual Heated, Power Remote-Control, Foldable Mirrors | - | • | • | |
| /ariable Intermittent Wipers, Rear Window Wiper/Washer, Windshield Wiper De-Icer | • | • | • | |
| talogen Headlamps | • | • | • | |
| Fog Lamps | • | • | • | |
| Automatic Headlamp Cancel System | • | _ | • | |
| Projector Style Low Beam Headlamps | • | • | • | |
| ight Control System | _ | • | _ | _ |
| ight Emitting Diode (LED) Rear Taillamps | • | • | _ | _ |
| PACKAGES | | | | |
| Leather Package: Leather Seating Surfaces, Simulated Leather Door Trim, Leather-Wrapped Steering Wheel, Leather-Wrapped Shift Knob, Power 10-Way Driver Seat, Driver & Front Passenger Heated Seats, Driver & Front Passenger Headrest Tilt Adjustment | _ | _ | 0 | С |
| Limited Package: Leather Package plus P225/65R17 All-Season Radials, 17" Alloy Wheels, Wheel Locks, Rear Spoiler, Automatic Climate Control, Rear Auxiliary Heater, Power 4-Way Front Passenger Seat, Simulated Woodgrain Interior Trim, Dual Illuminated Vanity Mirrors, Electrochromic Rear View Mirror w/Digital Compass, Integrated Garage Doo Opener, Outside Temperature Gauge, Multi-Information Display, Vehicle Anti-Theft System, JBL AM/FM Cassette/CD Changer, 8-Speakers, Diversity Antenna, Steering Wheel Audio Controls, Power Moonroof, Light Control System, Limited Badging | r — | _ | _ | C |

head/side curtain airbag Supplemental Restraint System (SRS) which activate only in a side-impact collision of sufficient magnitude to inflate the bags. Roll-sensing airbags are designed to deploy at severe tilt degree roll or lateral G-force. Seatbelts must be worn at all times by all occupants.

2007 Highlander Specifications

| MECHANICAL |
|---|
| Engine 3.3 Litre, V6, DOHC, 24-Valve, Variable Valve Timing w/intelligence (VVT-i), Sequential Multiport Electronic Fuel Injection |
| Compression Ratio 10.8:1 |
| Horsepower |
| 208 hp (155 kW) @ 5600 rpm (gas engine only) |
| 215 hp (160 kW) @ 5600 rpm |
| |
| 212 lb.ft. (287 N.m.) @ 4400 rpm (gas engine only) |
| 222 lb.ft. (301 N.m.) @ 3600 rpm |
| Electric Motor Front: Permanent Magnet Motor, 165 hp (123 kW) @ 4500 rpm, 247 lb.ft. (335 N.m.) @ 0–1500 rpm, AC 650V |
| Rear: Permanent Magnet Motor, 67 hp (50 kW) @ 4610–5120 rpm, 96 lb.ft. (130 N.m.) @ 0–610 rpm, AC 650V |
| Hybrid System Net Horsepower: 268 hp (200 kW)† |
| Net Torque: Output will vary depending upon HV Battery state and demand on vehicle |
| HV Battery Sealed Nickel-Metal Hydride (Ni-MH) |
| Maximum Power Output: 45 kW |
| Voltage: 288V |
| Suspension |
| Front: MacPherson Gas Struts, Gas Shock Absorbers, Coil Springs, Stabilizer Bar, Anti-Vibration Subframe |
| Rear: MacPherson Gas Struts, Gas Shock Absorbers, Coil Springs, Stabilizer Bar, Anti-Vibration Subframe |
| Drivetrain Vehicle Dynamics Integrated Management (VDIM), Vehicle Stability Control (VSC), Traction Control (TRAC), On Demand Electronic 4WD |
| Full-Time 4WD, Vehicle Stability Control (VSC), Traction Control (TRAC) |
| Transmission Electronically Controlled Continuously Variable Transmission (ECVT), Power Split Device, Transmission Cooler |
| 5-Speed, Automatic, Electronically Controlled Transmission (ECT), Overdrive Cancel Switch, Lock-Up Torque Converter, Transmission Cooler |
| Brakes Power-Assisted, Front Ventilated Discs, Rear Discs, Antilock Braking System (ABS) w/Electronic Brake-force Distribution (EBD), Brake Assist (BA) |
| Integrated Regenerative Braking System, Electronically Controlled Hydraulic Braking System (ECB2) |
| Steering Electric Rack & Pinion Power Steering |
| Rack & Pinion w/Variable Power Assist |
| Tires P225/65R17, All-Season Radials, Full-Size Spare w/Alloy Wheel |
| P225/70R16, All-Season Radials, Full-Size Spare w/Alloy Wheel |
| |

• = Standard \circ = Optional – = Not Available [†] The maximum output indicates engine

Toyota Canada Inc. Every effort has been made to ensure the specifications and equipment shown are accurate based on information available at time of printing. In some cases, certain changes in standard equipment, options or product delays may occur which would not ** These estimates are based on the Government of Canada's approved criteria and testing methods. be reflected in this brochure. Toyota Canada Inc. reserves the right to make these changes without notice or obligation. The Toyota website toyota.ca - or your Toyota Dealer is your best source for up-to-date information.

| Hybrid | | | | | | | | | |
|--|---|--|---|--|----------------------------|---|---|------------------|------------------|
| Limited | 4WD V6 | 4WD V6 (7-Seats) | | | | Hybrid | Hybrid Limited | 4WD V6 | 4WD \ (7-Seat |
| | | | DIMENSIONS | mm (in.) | | | | | |
| | Length | 4710 (185.4) | | • | ٠ | - | - | | |
| | | | | 4689 (184.6) | | - | - | ٠ | • |
| ٠ | ٠ | • | Width | 1826 (71.9) | | • | ٠ | ٠ | ٠ |
| • • • | Height (Unloaded) | 1735 (68.3) | | _ | - | • | • | | |
| | | 1745 (68.7) | | ٠ | ٠ | - | _ | | |
| | Wheelbase | 2715 (106.9) | | • | ٠ | • | • | | |
| • | _ | - | Tread | Front: 1575 (62.0) | | • | • | • | • |
| _ | • | • | | Rear: 1555 (61.2) | | • | • | • | • |
| | | | Seating Capacity | 5 | | • | | • | |
| | | | Searing Capacity | 7 | | • | • | _ | • |
| | | | Ground Clearance | 185 (7.3) | | _ | | | |
| - | • | • | | | • I. • • • • • • • • • • | • | • | • | • |
| | Headroom | Front: 1019 (40.1) | 2nd Row: 983 (38.7) | • | - | - | - | | |
| | | Front: 980 (38.6) | 2nd Row: 960 (37.8) | - | ٠ | - | - | | |
| • | - | - | | - | 3rd Row: 922 (36.3) | - | • | - | - |
| | | | | Front: 1019 (40.1) | 2nd Row: 1012 (39.8) | - | - | • | • |
| ٠ | - | - | | | 3rd Row: 820 (32.2) | - | - | - | • |
| | | | | Front: 980 (38.6) | 2nd Row: 988 (38.9) | - | - | - | С |
| • | _ | _ | - | | 3rd Row: 820 (32.2) | - | - | - | С |
| • | _ | _ | Legroom | Front: 1090 (42.9) | 2nd Row: 879 (34.6) | • | ٠ | - | - |
| | | | | | 3rd Row: 767 (30.2) | - | ٠ | - | - |
| | | | | Front: 1035 (40.7) | 2nd Row: 925 (36.4) | - | - | ٠ | • |
| • | - | - | | | 3rd Row: 767 (30.2) | - | - | - | • |
| ٠ | - | - | Shoulder Room | Front: 1470 (57.9) | 2nd Row: 1448 (57.0) | • | • | ٠ | • |
| ٠ | - | - | | | 3rd Row: 1352 (53.2) | _ | • | _ | • |
| | | | GROSS VEHICLE WEIGH | T kg (lb) | | | | | |
| | | | | 2575 (5675) | | | | _ | _ |
| • • • | | | | | - | | | | |
| • | • | • | | 7431 (5360) | | _ | _ | | |
| • | • | • | | 2431 (5360) | | - | - | ٠ | • |
| • | • | • | CURB WEIGHT | kg (lb) | | - | - | • | • |
| • | • | • | CURB WEIGHT | kg (lb) 1900 (4188) | | - | - | _ | - |
| • | • | • | CURB WEIGHT | kg (lb) 1900 (4188) 1925 (4244) | | • | - | - | - |
| • | • | • | CURB WEIGHT | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) | | • | - - • | _ | - |
| • | • | • | | <i>kg (lb)</i> 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) | | - - - - | - - - - | - | - |
| • | • | • | CURB WEIGHT TOWING CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) | | - - - | - - - - | - | - |
| • | • | • | | <i>kg (lb)</i> 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) | | - - - - | - • - | - | - |
| • | • | • | | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) | | - | | - | - |
| • | • | • | TOWING CAPACITY | <i>kg (lb)</i> 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) <i>kg (lb)</i> 1587 (3500) | | | - | - | |
| • | • | • | TOWING CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) | | - | - • - • • • | - | |
| • | • | • | TOWING CAPACITY PAYLOAD*** | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) | | | - • - • | - | |
| • | • | • | TOWING CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) | Front Costs | - | - | - | - |
| • | • • • • • • | • | TOWING CAPACITY PAYLOAD*** | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind | | - - - - | - - - - - | - - - - | - |
| • | • | • | TOWING CAPACITY PAYLOAD*** | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind | 2nd Row Seats | - - - - - | | - | - |
| • • • • • | • | • • • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind | 2nd Row Seats | - - - - - - | - - - - - - - - - - - - - - - - - - - | - - - - | - |
| • • • • | • | • | TOWING CAPACITY PAYLOAD*** | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind | 2nd Row Seats | - - - - - - - - - - - - - - - - - - - | - - - - - - - - - - - - - - - - - - - | - - - - | - |
| • • • • • • • • | • | • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind | 2nd Row Seats | | | - - - - | - |
| • • • • • • • | • • | • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind | 2nd Row Seats | - - - - - - - - - - - - - - - - - - - | - - - - - - - - - - - - - - - - - - - | - - - - | - |
| • • • • • • | • • • • | • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind cd 0.34 m (ft.) | 2nd Row Seats | | - - - - - - - - - - - - - - - - - - - | - - - - | - |
| • | • | • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG TURNING CIRCLE | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind cd 0.34 m (ft.) 11.4 (37.4) | 2nd Row Seats | | - - - - - - - - - - - - - - - - - - - | - - - - | - |
| • - - • • | • | • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind 0.297 (10.5) Behind 1.124 (37.4) 11.4 (37.4) litres (gal) | 2nd Row Seats | | | - - - - | - |
| • - • • | • • • • • • | • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG TURNING CIRCLE | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind 0.297 (10.5) Behind 1.124 (37.4) Example 1.2 11.4 (37.4) litres (gal) 65.0 (14.3) | 2nd Row Seats | | | - - - - | - |
| • - • • • | • | • • • • • • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG TURNING CIRCLE FUEL CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind 0.34 m (ft.) 11.4 (37.4) litres (gal) 65.0 (14.3) 72.5 (15.9) | 2nd Row Seats | | | - - - - | - |
| • - • • • • | • | • • • • • • • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG TURNING CIRCLE | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind 0.297 (10.5) Behind 1.124 (37.4) 11.4 (37.4) litres (gal) 65.0 (14.3) 72.5 (15.9) ATING** | 2nd Row Seats | | | - - - - | - |
| • - • • • • | • • • • • • • • • • • • • • • | • • • • • • • • • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG TURNING CIRCLE FUEL CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind 0.34 m (ft.) 11.4 (37.4) litres (gal) 65.0 (14.3) 72.5 (15.9) | 2nd Row Seats | | | - - - - | - |
| • - - • • • • • • • • • • • • • • • • • | • • • • • • • • • • • • • • • • • • • | • • • • • • • • • • • • • • • • | TOWING CAPACITY PAYLOAD*** CARGO CAPACITY COEFFICIENT OF DRAG TURNING CIRCLE FUEL CAPACITY | kg (lb) 1900 (4188) 1925 (4244) 1760 (3880) 1785 (3935) kg (lb) 1587 (3500) kg (lb) 390 (860) 526 (1159) m ³ (cu.ft.) 2.282 (80.6) Behind 1.124 (39.7) Behind 0.297 (10.5) Behind 0.297 (10.5) Behind 1.124 (37.4) 11.4 (37.4) litres (gal) 65.0 (14.3) 72.5 (15.9) ATING** | 2nd Row Seats | | | - - - - | |

The actual fuel consumption of this vehicle may vary. Refer to the Government of Canada publication EnerGuide Fuel Consumption Guide.

*** Payload = Passengers, Equipment, Luggage and Cargo