



Dimensions and Weight		GX 550 Signature/Premium	GX 550 Luxury/Executive	GX 550 Overtrail/Overtrail+
Overall	Length mm (in.)	5,005 (197.05)	5,005 (197.05)	5,005 (197.05)
	Width mm (in.)	1,980 (77.95)	1,980 (77.95)	2,000 (78.74)
	Height mm (in.)	1,920 (75.59)	1,915 (75.39)	1,935 (76.18)
Wheelbase	mm (in.)	2,850 (112.20)	2,850 (112.20)	2,850 (112.20)
Tread	Front mm (in.)	1,667 (65.63)	1,667 (65.63)	1,687 (66.42)
	Rear mm (in.)	1,668 (65.67)	1,668 (65.67)	1,688 (66.46)
Effective Head Room: Executive with Dynamic Sky Panorama Glass Roof	Front mm (in.)	1,001 (39.39)	1,001 (39.39) Executive: 1,024 (40.31)	1,001 (39.39)
	Rear 2 <sup>nd</sup> Row mm (in.)	1,096 (43.15)	1,096 (43.15) Executive: 1,063 (41.85)	1,096 (43.15)
	Rear (3 <sup>rd</sup> Row) mm (in.)	900 (35.45)	900 (35.45) Executive: 896 (35.28)	n/a
Effective Leg Room:	Front mm (in.)	1046 (41.18)	1046 (41.18)	1046 (41.18)
	Rear (2 <sup>nd</sup> Row) mm (in.)	933 (36.73)	933 (36.73)	933 (36.73)
	Rear (3 <sup>rd</sup> Row) mm (in.)	810 (31.89)	810 (31.89)	n/a
Shoulder Room:	Front mm (in.)	1,511.6 (59.51)	1,511.6 (59.51)	1,511.6 (59.51)
	Rear (2 <sup>nd</sup> Row) mm (in.)	1,452.2 (57.17)	1,452.2 (57.17)	1,452.2 (57.17)
	Rear (3 <sup>rd</sup> Row) mm (in.)	1,390.8 (54.76)	1,390.8 (54.76)	n/a
Hip Room:	Front mm (in.)	1,434.2 (56.46)	1,434.2 (56.46)	1,434.2 (56.46)
	Rear (2 <sup>nd</sup> Row) mm (in.)	1,432 (56.39)	1,432 (56.39)	1,432 (56.39)
	Rear (3 <sup>rd</sup> Row) mm (in.)	1,151 (45.30)	1,151 (45.30)	n/a
Interior: Normal Roof (NR) Moon Roof (MR) Dynamic Sky Panorama Glass Roof (DS)	Length (2 <sup>nd</sup> Row) mm (in.)	1,940 (76.37)	1,940 (76.37)	1,940 (76.37)
	Length (3 <sup>rd</sup> Row) mm (in.)	2,697 (106.18)	2,697 (106.18)	n/a
	Width mm (in.)	1,575.3 (62.02)	1,575.3 (62.02)	1,575.3 (62.02)
	Height mm (in.)	1,189 (46.80)	1,189 (46.80) Executive: 1,200 (47.25)	1,189 (46.80)
Couple Distance:	Front to Rear (2 <sup>nd</sup> Row) mm (in.)	951 (37.44)	951 (37.44)	951 (37.44)
	Front to Rear (3 <sup>rd</sup> Row) mm (in.)	1,777 (69.96)	1,777 (69.96)	n/a
Seating Capacity	Person	Bench: 7 Captain's Chairs: 6	Bench: 7 Captain's Chairs: 6	5
Overhang	Front mm (in.)	960 (37.80)	960 (37.80)	960 (37.80)
	Rear mm (in.)	1,995 (47.05)	1,995 (47.05)	1,995 (47.05)
Coefficient of Drag		0.399	0.399	0.399
Min. Running Ground Clearance	mm (in.)	220 (8.66)	220 (8.66)	225 (8.86)
Location of Min. Running Ground Clearance		Under Cover		
Angle of Approach	Degrees	26		
Angle of Departure	Degrees	21		
Breakover Angle	Degrees	23	23	24



## 2024 GX Specifications - Lexus Canada



Dimensions and Weight		GX 550 Signature/Premium	GX 550 Luxury/Executive	GX 550 Overtrail/Overtrail+
Curb Weight (Emission Regulation)	Front (lb.)	2,915-2,925	2,960	3,035-3,045
	Rear (lb.)	2,660-2,680	2,695-2,750	2,640-2,660
	Total (lb.)	5,585-5,606	5,565-5,710	5,675-5,705
Curb Weight (FMVSS)	Front (kg.)	1320 - 1345	1320 - 1345	1320 - 1345
	Rear (kg.)	1145 - 1230	1145 - 1230	1145 - 1230
	Total (kg.)	2480 - 2570	2480 - 2570	2480 - 2570
Gross Vehicle Weight (GVWR)	Total (kg./ lb.)	3,190 (7,030)	3,140 (6,920)	3,250 (7,165)
Cargo Space (SAE): 2-Row Overtrail/Overtrail+ 3-Row Signature, Premium, Luxury, Executive	All Seats Up	292 L (10.3 cu. ft.)	292 L (10.3 cu. ft.)	1,291 (45.6 cu. ft.)
	Max Cargo	3 <sup>rd</sup> Row Folded: 1,138 L (40.2 cu. ft.)	3 <sup>rd</sup> Row Folded: 1,138 L (40.2 cu. ft.)	2 <sup>nd</sup> Row Folded: 2,563 L (90.5 cu. ft.)
		Both Folded: 2,178 L (76.9 cu. ft.)	Both Folded: 2,178 L (76.9 cu. ft.)	
Towing Capacity (UPDATED)	Lb.	9,063	Luxury: 8,020 Executive: 7,601	9,063
Engine		GX 550 Signature/Premium	GX 550 Luxury/Executive	GX 550 Overtrail/Overtrail+
Engine Type		3.4-Liter V6 Twin Turbo		
Valve Mechanism		24-valve DOHC, Chain Drive (with Dual VVT-i)		
Bore x Stroke	mm (in.)	85.5 (3.37) x 100.0 (3.94)		
Displacement	cm <sup>3</sup> (cu. in.)	3,445 (210.23)		
Compression Ratio		10.3		
Fuel Injection System		D-4ST		
Fuel Type		Gasoline		
Fuel Tank Capacity	Litres	80		
Recommended Octane		Premium		
Output	hp @ rpm	349 @ 4,800-5,200		
Torque*	lb.-ft. @ rpm	479 @ 2,000-3,600		
NRCAN Fuel Consumption ratings	Combined	13.5 L/100 km		
	Highway	11.2 L/100 km		
	City	15.2 L/100 km		
Performance		GX 550 Signature/Premium	GX 550 Luxury/Executive	GX 550 Overtrail/Overtrail+
Max. Speed	(km/h)	175		
Acceleration (0-60 mph)	(sec.)	6.5		
Minimum Turning Radius	Tire m (ft)	6.0 (19.7)		
	Body m (ft)	6.4 (21.0)		



Chassis		GX 550 Signature/Premium	GX 550 Luxury/Executive	GX 550 Overtrail/Overtrail+
Transaxle	Type	Automatic		
Transaxle Gear Ratio	1st	4.923		
	2nd	3.257		
	3rd	2.349		
	4th	2.349		
	5th	1.532		
	6th	1.193		
	7th	1.000		
	8th	0.801		
	9 <sup>th</sup>	0.661		
	10th	0.613		
		Reverse	4.307	
Final Drive Gear Ratio		3.307		
Differential Gear Ratio (Front/Rear)		-/3.307		
Suspension Type	Front	Double Wishbone		
	Rear	Four Link with Coil Spring		
Brake Type	Front	Ventilated Disc with Fixed Caliper 4-Cylinder		
	Rear	Ventilated Disc with Floating Caliper 1-Cylinder		
Brake Size (Disc outer diameter x thickness)	Front mm (in.)	354 x 32 (13.94 x 1.26)		
	Rear mm (in.)	335 x 20 (13.19 x 0.79)		
Parking Brake Type of Control and Location		EPB Center Console Switch		
Lock to Lock		3.2		
Steering Gear Type		Rack & Pinion		
Power Steering Type		Electric Power Steering		