TOYOTA

2025 4Runner
TCI Product Information

ENGINE	i-FORCE	i-FORCE MAX
Type, Materials	T24A-FTS 2.4-liter 4-cylinder Turbocharged, Double Overhead Cam (DOHC) 16-Valve, D-4S Fuel Injection	T24A-FTS 2.4-liter 4-cylinder Hybrid Turbocharged, Double Overhead Cam (DOHC) 16-Valve, D-4S Fuel Injection
Displacement	2,393 cc	
Bore x Stroke	Φ87.5 x 99.5 mm	
Compression Ratio	11:1	
Horsepower	278 hp @ 6000 rpm	326 hp @ 6000 rpm
Torque	317 lb-ft @ 1700 rpm	465 lb-ft @ 1700 rpm
Hybrid battery	-	1.87-kWh NiMH
Ignition System	DIS (Direct) with iridium-tipped spark plugs	
Fuel System	D-4ST	
Fuel	Regular	

DRIVETRAIN	
Layout	Front engine with part-time four-wheel drive Front engine with full-time four-wheel drive
Transmission Type	8-speed Automatic Transmission
Gear Ratios	
1st	4.41
2nd	2.80
3rd	1.95
4th	1.51
5th	1.27
6th	1.00
7th	0.79
8th	0.65
Reverse	3.64
4x4 Transfer Case Ratio (high/low)	1.00:1 / 2.57:1
Final Drive Ratio	3.583

2025 4Runner
TCI Product Information

FUEL CONSUMPTION (City/Highway/Combined) *	
i-FORCE (Part-time 4WD)	12.4 / 9.6 / 11.2 L/100km
i-FORCE Limited (Full-time 4WD)	12.0 / 9.9 / 11.1 L/100km
i-FORCE MAX (Part-time 4WD)	10.3 / 9.5 / 9.9 L/100km
i-FORCE MAX Platinum (Full-time 4WD)	10.5 / 9.7 / 10.1 L/100km

*NRCan estimated numbers. Actual fuel consumption will vary.

CHASSIS AND BODY				
Suspension				
Front	Independent double-wishbone front suspension with stabilizer bar and twin-tube shock absorbers			
Rear (coil)	Multi-link rear suspension with coil springs and outboard-mounted twin-tube shock absorbers			
Steering				
Type	Electronic Power Steering (EPS); power-assisted rack-and-pinion			
Turns (lock-to-lock)	3.25 turns			
Turning Radius (ft)	19.7ft			
Angles				
Grade	**SR5**	**SPT/LTD/PLT**	**TRD O/R**	**PRO/TH**
Approach	18 deg	18 deg	19 deg	33 deg
Departure	22 deg	22 deg	24 deg	24 deg
Breakover	23 deg	24 deg	24 deg	24 deg
Ground clearance	206 mm	224 mm	231 mm	257 mm
Wheel Type, Material and Tire Size				
SR5	18-in dark gray metallic alloy wheels w/ 245/70R18 tires			
TRD Sport (Premium)	20-in machine finished alloy wheels w/ 265/55R20 tires			
TRD Off-Road (Premium)	18-in machine finished alloy wheels w/ 265/70R18 tires			
Limited	20-in machine finished alloy wheels w/ 265/55R20 tires			
Trailhunter	18-in flat bronze finished alloy wheels w/ 265/70R18 tires			
TRD Pro	18-in flat black finished alloy wheels w/ 265/70R18 tires			
Platinum	20-in black alloy wheels w/ 265/55R20 tires			
Brake System				

Parking Brake type	EPB (Electronic Parking Brake)
Front	17” Opposed
Rear	17” Floating with EPB motor unit

EXTERIOR DIMENSIONS				
Grade	**SR5**	**SPT/LTD/PLT**	**TRD O/R**	**PRO/TH**
Overall Length	4,950 mm	4,950 mm	4,950 mm	4,950 mm
Overall Width	1,980 mm	1,980 mm	1,980 mm	2,030 mm
Overall Height	1,845 mm	1,860 mm	1,870 mm	1,920 mm
Wheelbase	2,850 mm	2,850 mm	2,850 mm	2,850 mm

INTERIOR DIMENSIONS	
Seating Capacity	SR5, Limited: 7 seats All other grades: 5 seats
Headroom (mm) Front/Rear/3rd row	Without moonroof: 1,008 / 960 / 897 mm With moonroof: 973 / 960 / 897 mm
Legroom (mm) Front/Rear/3rd row	1,062 / 884 / 808 mm
Shoulder Room (mm) Front/Rear	1,473 mm / 1,468 mm
Hip Room (mm) Front/Rear	1,402 mm / 1,425 mm

WEIGHTS AND CAPACITIES								
Powertrain	i-FORCE				i-FORCE MAX			
Grade	SR5	SPT	ORP	LTD	ORP	PRO	TH	PLT
Curb Weight (lbs.)	4,685	4,850	4,850	4,970	5,225	5,455	5,500	5,390
Curb Weight (kg)	2,125	2,200	2,200	2,254	2,370	2,474	2,495	2,445
GVWR (lbs.)	6,075	6,395	6,240	6,395	6,505	6,505	6,505	6,505
GVWR (kg)	2,756	2,901	2,830	2,901	2,951	2,951	2,951	2,951
Towing Capacity	2,722 kg / 6,000 lbs.							
Fuel Capacity	72 L							
Engine Oil	5.6 L (with filter)							

CARGO CAPACITIES

Number of seats	5-seat	7-seat
behind 1st row	2,554 L (80.2 cu.ft)	2,381 L (84.1 cu.ft)
behind 2nd row	1,371 L (48.4 cu.ft)	1,269 L (44.8 cu.ft)
behind 3rd row	-	343 L (12.1 cu.ft)

AVAILABLE EXTERIOR COLOURS

- White
- Wind Chill Pearl*
- Cutting Edge Silver
- Underground
- Black
- Supersonic Red*
- Heritage Blue
- Mudbath
- Everest

*Extra cost colour

BASIC LIMITED WARRANTY COVERAGE

- 3-year/60,000km Basic
- 5-year/100,000km Powertrain
- 8-year/160,000km Hybrid-Related Component Coverage
- 10-year/240,000km Hybrid Battery