



| ENGINE | |
|--|---|
| Type, Materials | 2.4-litre, 4-cylinder, boxer, aluminum alloy block and head |
| Valve train | DOHC 4-valves per cylinder with Dual Variable Valve Timing |
| Displacement | 2387cc |
| Bore x Stroke | 94 x 86 mm |
| Compression Ratio | 12.5:1 |
| Horsepower | 228 hp @ 7,000 rpm (SAE NET) |
| Torque | 184 lb-ft @ 3,700 rpm |
| Fuel System | D-4S (Direct and Sequential Port Injection) |
| Required Fuel | Premium Fuel |
| Estimated Fuel Consumption* (city/highway/combined) | GR86 6 Speed MT – 11.9/8.7/10.5 L/100 km GR86 6 Speed AT – 11.1/7.7/9.6 L/100 km |

*Estimated fuel consumption - Actual figures will vary.

| DRIVETRAIN | | |
|----------------------------------|----------------|-------------------|
| Transmission Type | 6-Speed Manual | 6-Speed Automatic |
| Gear Ratios | | |
| 1 st | 3.626 | 3.538 |
| 2 nd | 2.189 | 2.060 |
| 3 rd | 1.541 | 1.404 |
| 4 th | 1.213 | 1.00 |
| 5 th | 1.000 | 0.713 |
| 6 th | 0.767 | 0.582 |
| Reverse | 3.437 | 3.168 |
| Differential Ratio | 4.10 | 3.90 |
| Torsen Limited-Slip Differential | | |

| CHASSIS AND BODY | |
|--------------------|--|
| Suspension - Front | Sport-tuned independent MacPherson strut front suspension |
| - Rear | Sport-tuned independent double wishbone style multi-link rear suspension |

**TOYOTA**

2026 GR86 Product Information

| | |
|---------------------------|---|
| Stabilizer Bar - Diameter | 18.3 mm/14 mm (front/rear) |
| Steering - Type | Electric Power Steering (EPS) |
| - Overall Ratio | 13.5 |
| - Turns (lock-to-lock) | 2.5 |
| - Turning Circle Diameter | 10.8 m/35.4 ft. (curb-to-curb) |
| Brakes - Front Type | Power-Assisted Ventilated Disc |
| - Front Diameter | 295 mm / 11.6 in. |
| - Rear Type | Power-Assisted Ventilated Disc |
| - Rear Diameter | 290 mm/ 11.4 in. |
| - Parking | Center hand brake |
| Wheel Size | GR86: 17 x 7.5 in. GR86 Premium: 18 x 7.5 |
| Wheel Type and Material | Alloy |
| Tire Size | GR86: 215/45 R17 GR86 Premium: 215/40 R18 |
| Tire Type | GR86: Michelin Primacy HP GR86 Premium: Michelin Pilot Sport 4 |
| Spare Tire/Wheel | None (Tire Repair Kit) |

| EXTERIOR DIMENSIONS | |
|-------------------------|---------------------------------|
| Wheelbase | 2,575 mm. (101.4 in.) |
| Overall Length | 4,265 mm. (167.9 in.) |
| Overall Width | 1,775 mm. (69.9 in.) |
| Overall Height | 1,310 mm. (51.6 in.) |
| Tread Width, Front/Rear | 1,519/1,550 mm. (59.8/61.0 in.) |
| Ground Clearance | 130 mm. (5.1 in.) |
| Coefficient of Drag | 0.276 |



| INTERIOR DIMENSIONS | |
|---------------------------|-------------------------------------|
| Seating Capacity | 4 |
| Headroom, Front/Rear | 939.8/850.9 mm. (37.0/33.5 in.) |
| Legroom, Front/Rear | 1,054.1/759.5 mm. (41.5/29.9 in.) |
| Shoulder Room, Front/Rear | 1,361.4/1,313.2 mm. (53.6/51.7 in.) |
| EPA Passenger Volume | 2,186 litres (77.19 cu. ft.) |
| Cargo Volume (Trunk) | 178 litres (6.26 cu. ft.) |

| WEIGHTS AND CAPACITIES | |
|----------------------------|--|
| Curb Weight | Base MT – 1,279.13 kg. (2,820 lbs.) Premium MT, Hakone – 1,286.84 kg. (2,837 lbs.) Premium AT – 1,306.8 kg. (2,881 lbs.) |
| Fuel Capacity | 50 litres (13.2 gal.) |
| Engine Oil Capacity | 6.2 quarts |
| Engine Oil w/Filter Change | 5.1–5.3 quarts |

| AVAILABLE EXTERIOR COLOURS |
|--|
| <ul style="list-style-type: none">• Steel• Halo*• Track bRed*• TRUENO Blue• Pavement• Raven• Yuzu Yellow |

*Extra cost colour

| BASIC LIMITED WARRANTY COVERAGE |
|---|
| <ul style="list-style-type: none">• 3-year/60,000km Basic• 5-year/100,000km Powertrain |