



## 2026 LX Specifications



Dimensions and Weight			LX 600	LX 700h
Overall	Length mm (in.)		5085 (200.2) <sup>*1</sup> , 5095 (200.59)	
	Width mm (in.)		1990 (78.35)	
	Height mm (in.)		1885 (74.21) <sup>*3</sup> , 1895 (74.61) <sup>*4</sup>	1885 (74.21) <sup>*2, *3</sup> , 1895 (74.61) <sup>*4, *12</sup>
Wheelbase	mm (in.)		2850 (112.2)	
Tread	Front mm (in.)		1677 (66.02)	
	Rear mm (in.)		1678 (66.06)	
Head Room	Front mm (in.)		960 (37.8)	
	Rear mm (in.)	2nd-row seat	990 (38.98)	990 (38.98), 985 (38.78) <sup>*5</sup>
		3rd-row seat	895 (35.24)	
Leg Room	Front mm (in.)		1045 (41.14)	
	Rear mm (in.)	2nd-row seat	930 (36.61)	930 (36.61), 860 (33.86) <sup>*5</sup>
		3rd-row seat	790 (31.1)	
Shoulder Room	Front mm (in.)		1560 (61.42)	
	Rear mm (in.)	2nd-row seat	1495 (58.86)	
		3rd-row seat	1425 (56.10)	
Hip Room	Front mm (in.)		1515 (59.65)	
	Rear mm (in.)	2nd-row seat	1495 (58.86)	
		3rd-row seat	1245 (49.02)	1140 (44.88)
Interior	Length mm (in.)		2755 (108.46) <sup>*6</sup> , 1950 (76.77) <sup>*7</sup>	2755 (108.46) <sup>*6</sup> , 2005 (78.94) <sup>*5</sup> , 1950 (76.77) <sup>*7</sup>
	Width mm (in.)		1630 (64.17)	
	Height mm (in.)		1190 (46.85) <sup>*8</sup> , 1210 (47.64)	



## 2026 LX Specifications



Dimensions and Weight		LX 600	LX 700h	
Couple Distance	Front to Rear mm (in.)	950 (37.4)		
Seating Capacity	2nd-row specification (person)	5	4 <sup>*5</sup> , 5	
	3rd-row specification (person)	7	7	
Overhang	Front mm (in.)	1035 (40.75) <sup>*1</sup> , 1040 (40.94)		
	Rear mm (in.)	1215 (47.83)		
Min. Running Ground Clearance	mm (in.)	200 (7.87) <sup>*3</sup> , 205 (8.07) <sup>*4</sup>	200 (7.87) <sup>*3</sup> , 205 (8.07) <sup>*4, *13</sup>	
Location of Min. Running Ground Clearance		Engine Under Cover		
Angle of Approach	Degrees	21 <sup>*1</sup> / 22 <sup>*3</sup> / 23 <sup>*4</sup>	21 <sup>*1</sup> / 22 <sup>*2*3</sup> / 23 <sup>*4*12</sup>	
Angle of Departure	Degrees	22 <sup>*1*4</sup> 2 <sup>*4</sup>	21	
Curb Weight (Emission Regulation)	Front (lb.)	3,100 - 3,110	3,175 - 3,230	
	Rear (lb.)	2,680 - 2,835	3,010 - 3,085	
	Total (lb.)	5,790 - 5,945	6,230 - 6,260	
Curb Weight (FMVSS)	Front (lb.)	3,086 - 3,108	3,174 - 3,229	
	Rear (lb.)	2,645 - 2,788	2,932 - 3,053	
	Total (lb.)	5,754 - 5,875	6,128 - 6,261	
Gross Vehicle Weight (GVWR)	Total (lb.)	7,230	7,450	
Towing capacity	With Towing Package (lb)	8,000		
Cargo Space (SAE)	(cu. ft.)	All Seats Up (2-row model)	46	30.98 <sup>*16</sup>
		All Seats Up (3-row model)	11	7.23 <sup>*16</sup>
		Max. Cargo (2-row)	71 <sup>*9</sup>	62.56 <sup>*14</sup>
		Max. Cargo (3-row)	64 <sup>*10</sup> , 44 <sup>*11</sup>	62.43 <sup>*14</sup>



## 2026 LX Specifications



Dimensions and Weight		LX 600	LX 700h
Fuel Tank Capacity	Litres (US Gallons)	80 (21.14)	68 (17.97)

\*1: F SPORT \*2: Vehicles with 265/65R18 tires \*3: Vehicles with 265/55R20 tires \*4: Vehicles with 265/50R22 tires  
 \*5: Ultra Luxury model \*6: 7-seater \*7: 5-seater \*8: With moon roof \*9: Rear seat folded \*10: 2nd and 3rd-row seats folded  
 \*11: 3rd-row seat folded \*12: Vehicles with 265/70R18 tires \*13: Overtrail model \*14: Without rear entertainment system and when front seat position is front most

Engine		LX 600	LX 700h
Engine Type		V35A-FTS	
No. of Cylinders & Arrangement		6-cylinder, V type	
Valve Mechanism		24-Valve, DOHC, Chain Drive	
Bore x Stroke	(in.)	3.37 x 3.94	
Displacement	cu.in. (cm <sup>3</sup> )	3,445 (210.23)	
Compression Ratio		10.5	
Fuel Injection System		EFI (D-4ST)	
Fuel Type		Premium	
Recommended Octane Rating		95 or more (Octane)	
Output	hp @ rpm	409 @ 5,200	457 @ 5,200
Torque	lb.-ft. @ rpm	479 @ 2,000	583 @ 2,400
Manufacturer Estimated Fuel Consumption (L/100 km)	City	14.2	12.5
	Highway	10.8	10.7
	Combined	12.7	11.7
Hybrid Battery		LX 600	LX 700h
Battery Type		-	Nickel-Metal Hydride Battery
Nominal Voltage	(kW)	-	288
Number of Battery Cells	(Nm)	-	240
Performance		LX 600	LX 700h
Max. Speed <sup>*15</sup>	(km/h)	210	
Accel. <sup>*15</sup> (0-100 km/h)	(sec)	7.0	6.5

\*15: Toyota in-house measured figures



## 2026 LX Specifications



Chassis		LX 600	LX 700h
Transmission	Type	Automatic	
Transmission Gear Ratio	1st	4.923	
	2nd	3.257	
	3rd	2.349	
	4th	1.944	
	5th	1.532	
	6th	1.193	
	7th	1.000	
	8th	0.801	
	9th	0.661	
	10th	0.613	
	Reverse	4.307	
Chassis		LX 600	LX 700h
Differential Gear Ratio (Front / Rear)		- / 3.307	
Brake Type	Front	Ventilated Disc	
	Rear	Ventilated Disc	
Brake Size (Disc outer diameter x thickness)	Front mm (in.)	354 (13.94) / 32 (1.26)	
	Rear mm (in.)	335 (13.19) / 20 (0.79)	
Parking Brake Type of Control and Location		Electronic Parking Brake Center Console Switch	
Suspension Type	Front	Double-wishbone	
	Rear	Multi-link	
Min. Turning Radius	Curb to curb m (ft.)	6.0 (19.7)	
	Wall to wall m (ft.)	6.4 (21.0)	
Power Steering Type		EPS (Electronic)	



Colours
Ultra White*
Eminent White Pearl*
Atomic Silver
Manganese Lustre*
Caviar
Earth*
Nori Green Pearl

\*Additional Cost

Basic Limited Warranty Coverage
<ul style="list-style-type: none"><li>• 3-year/60,000km Basic</li></ul>
<ul style="list-style-type: none"><li>• 6-year/110,000km Powertrain, whichever comes first.</li></ul>
<ul style="list-style-type: none"><li>• 8-year/160,000km Hybrid-Related Component Coverage</li></ul>
<ul style="list-style-type: none"><li>• 10-year/240,000km Hybrid Battery</li></ul>