



2026 UX 300h Product Information

Exterior dimensions		UX 300h
Wheelbase	Mm (in.)	2,639 (103.9)
Overall Length	Mm (in.)	4,495 (176.9)
Overall Width	Mm (in.)	1,840 (72.4)
Overall Height	Mm (in.)	1,540 (60.6)
Front tread	Mm (in.)	1,550 (61.0)
Rear tread	Mm (in.)	1,550 (61.0)
Ground Clearance	Mm (in.)	160(6.3)
Coefficient of Drag	Cd	0.33

Interior dimensions		UX 300h
Seating Capacity	Person	5
Headroom	Front mm(in.)	907(35.7)
		889(35.0) (F SPORT DESIGN, F SPORT 2)
	Rear mm (in.)	924(36.4)
Leg Room	Front mm(in.)	1067(42.0)
	Rear mm(in.)	842(33.1)
Shoulder Room	Front mm(in.)	1397(55.0)
	Rear mm(in.)	1344(52.9)
Hip Room	Front mm(in.)	1367 (53.84)
	Rear mm(in.)	1329 (52.33)

Weight and Capacities		UX 300h
Curb Weight	kg(lbs.)	1,595 (3516.4)
GVWR	kg(lbs.)	2,110 (4651.7)
Cargo Capacity	All Seats Up L (cu. ft.)	487 (17.2)
Cargo bed Length	mm(in.)	793(31.2)
Cargo Bed Width (between wheel wells)	mm(in.)	1344(52.9)
Cargo Bed Depth	mm(in.)	513(20.2)

Engine		UX 300h
Type		2.0 L In-Line 4-Cylinder
Designation		M20A-FXS
Valvetrain		16-Valve DOHC, VVT-iE (intake), VVT-i (exhaust) for Atkinson cycle
Displacement	Cu. in. (cm ³)	121.3 (1,987)
Bore x Stroke	mm(in.)	80.5 (3.17) x 97.6 (3.84)
Compression Ratio		14.0:1
Fuel Injection System		EFI, D-4S
Horsepower	hp @ rpm	150 @ 6,000
Torque (gas engine)	lb.-ft. @ rpm	139 @ 4,400 - 5,200



2026 UX 300h Product Information

Electric Motor		UX 300h
Motor Type	Front	Permanent Magnet Synchronous Motor
	Rear	Permanent Magnet Motor
Max. Output	Front (hp)	111
	Rear (hp)	40
Max. Torque	Front (lb.-ft.)	151.9
	Rear (lb.-ft.)	62.0
Total Max. System Output*	Hp.	196

Battery		UX 300h
Battery Type		Li-ion
Nominal Voltage (V)		222
Number of Battery Cells		60

Performance		UX 300h
Max. Speed km/h (mph)		177 (110)
Acceleration (0-100 km/h) (sec.)		7.9

Chassis and Body		UX 300h
Transmission Type		Electronically Controlled Continuously Variable Transmission (ECVT)
Differential Gear Ratio	(Front/Rear)	3.605 /10.487
Suspension Type	Front	MacPherson Strut
	Rear	Trailing Wishbone
Steering Type		Rack & Pinion with column-mounted electric power assist
Turns, Lock to Lock		2.76
Turning Radius, curb	M (ft.)	5.2 (17.1)
Brakes	Type	Four-wheel power-assisted disc brakes
	Diameter Front Rear	12.01 in. ventilated disc 11.06 in. solid disc
Parking Brake (Type of Control / Location)		Electrical Switch Type, Instrument Panel
Wheels		18 x 7J alloy wheels (Premium, Luxury) 18 x 7J F SPORT alloy wheels (F SPORT Design, F SPORT 2)
Tires		225/50RF18 all-season run-flat



Colours
Ultra White*
Atomic Silver
Cloudburst Grey*
Iridium*
Caviar
Ultra White with Black Roof*
Ultrasonic Blue Mica 2.0 with Black Roof*
Cloudburst Grey with Black Roof*
Iridium with Black Roof*
Copper Crest with Black Roof*
Copper Crest *
Nori Green Pearl
*Additional charge

Basic Limited Warranty Coverage
<ul style="list-style-type: none">• 3-year/60,000km Basic
<ul style="list-style-type: none">• 6-year/110,000km Powertrain, whichever comes first.
<ul style="list-style-type: none">• 8-year/160,000km Hybrid-Related Component Coverage
<ul style="list-style-type: none">• 10-year/240,000km Hybrid Battery