



2026 Tacoma

Product Information



ENGINE		i-FORCE		i-FORCE MAX
Type, Materials	2.4-litre 4-cylinder Turbocharged, Double Overhead Cam (DOHC) 16-Valve, D-4S Fuel Injection		2.4-litre 4-cylinder Hybrid Turbocharged, Double Overhead Cam (DOHC) 16-Valve, D-4S Fuel Injection	
Transmission	8-speed A/T	6-speed M/T	8-speed	
Displacement	2,393 cc			
Bore x Stroke	87.5 x 99.5 mm			
Compression Ratio	11:1			
Horsepower	278 hp @ 6000 rpm	270 hp @ 5,400 rpm	326 hp @ 6000 rpm	
Torque	317 lb-ft @ 1700 rpm	310 lb-ft @ 2800 rpm	465 lb-ft @ 1700 rpm	
Ignition System	DIS (Direct) with iridium-tipped spark plugs			
Fuel System	D-4ST direct injection and port injection			
Recommended Fuel	87-octane or higher			
CAB MODEL				
Double Cab	Standard	Standard	Standard	
FUEL CONSUMPTION* (CITY/HWY/COMB) in L/100 KM				
SR5	12.4 / 9.8 / 11.2	N/A	N/A	
TRD Off-Road	12.4 / 10.2 / 11.8	13.0 / 10.2 / 11.8	N/A	
TRD Sport	12.4 / 10.2 / 11.8	13.0 / 10.2 / 11.8	N/A	
Note	*Manufacturer Estimated Fuel Consumption. Actual numbers will vary			
DRIVETRAIN				
Layout	4x4 front engine with part-time four-wheel drive			
Transmission Type	i-FORCE w/ 8-speed AT	i-FORCE w/ 6-speed MT	i-FORCE MAX w/ 8-speed AT	
Gear ratios				
1 st	4.413	4.784	4.413	
2 nd	2.808	2.423	2.808	
3 rd	1.950	1.443	1.950	
4 th	1.511	1.000	1.511	



2026 Tacoma

Product Information



5 th	1.274	0.777	1.274
6 th	1.000	0.643	1.000
7 th	0.793	-	0.793
8 th	0.651	-	0.651
Reverse	3.645	4.066	3.645
4x4	3.583	4.300	3.583
4x4 Transfer Case Ratio (high/low)		1.00:1 / 2.57:1	
CHASSIS AND BODY			
Suspension			
Front	Independent double-wishbone front suspension with stabilizer bar and twin-tube shock absorbers		
Rear (coil)	Multi-link rear suspension with coil springs and outboard-mounted twin-tube shock absorbers TRD Off-Road: TRD off-road suspension with monotube Bilstein shocks with piggy-back remote reservoir and End Stop Control Valve, Available Stabilizer with Disconnection Mechanism (SDM)		
Steering			
Type	Electronic Power Steering (EPS); power-assisted rack-and-pinion		
Overall ratio	16.9 (SR5) or 17.0 (TRD Sport, TRD Off-Road)		
Turns (lock-to-lock)	3.43 turns (SR5) or 3.25 turns (TRD Sport, TRD Off-Road)		
Turning Radius	Double Cab (5" bed)	6.43 – 6.77 m	
	Double Cab (6" bed)	6.98 – 7.35 m	
Wheel Type, Material and Tire Size			
SR5(+)	17-in styled alloy wheels w/ 245/70R17 tires		
TRD Off-Road (+)	17-in. alloy wheels with 265/70R17 all-terrain tires		
TRD Sport	18-in. alloy wheels with 265/65R18 tires		
TRD Off Road Premium	18" Off Road Alloy Wheels, 265/65R18 All Terrain tires	18" Off Road Alloy Wheels, 265/70R18 All Season Tires	
TRD Pro	18" TRD Pro Alloy Wheels, 265/70R18 Goodyear Territory RT Tires (33")		
Trailhunter	18" Trailhunter Alloy Wheels, 265/70R18 Goodyear Territory RT Tires (33")		
Limited	18" Limited Alloy Wheels, 265/65 R18 All Season Tires		



TOYOTA

2026 Tacoma Product Information



Brake system			
Model	SR5	TRD O/R and Sport	i-FORCE MAX (ALL)
Front	Ventilated disc, 12.6 in	Ventilated disc, 13.4 in	Ventilated disc, 13.4 in
Rear	Ventilated disc, 12.2 in	Ventilated disc, 12.2 in	Ventilated disc, 13.2 in
Parking Brake type	Electronic		
EXTERIOR DIMENSIONS (4x4 Double Cab)			
Body	Long bed (6")	Short bed (5")	
Wheelbase	145.1 in.	131.9 in.	
Overall Length	226.2 in.	213.0 in.	
Overall Width	77.9 in.		
Overall Height	73.8 in.* ¹ , 74.5 in.* ³ , 74.7 in.* ²	73.9 in.* ¹ , 74.6 in.* ^{2, 3}	
Inside Bed Length	73.5 in.	60.3 in.	
Inside Bed Depth	21.2 in.		
Inside Bed Width	53.0 in.		
At Tailgate	53.0 in.		
At Accessory Rail	56.4 in.		
Between Wheel wells	44.7 in.		
Tread Width (Front)	65.6 in.* ¹ 66.0 in.* ^{2,3}		
Tread Width (Rear)	65.6 in.* ¹ 66.0 in.* ^{2,3}		
Running Clearance	11.5 in. (TRD Off-Road)		
Approach Angle	33.8 deg (TRD Off-Road)		
Departure Angle w/ tow hitch	22.5 deg (TRD – Off-Road)		
Departure Angle w/o tow hitch	26.6 deg (TRD Off-Road)		
Breakover Angle	26.1 deg (TRD Off-Road)		
Note	*1: 245/70R17 tires *2: 265/70R17 tires (Off-Road) *3: 265/65R18 tires (TRD-SPORT)		
INTERIOR DIMENSIONS (4x4 Double Cab)			
Seating Capacity	5		



2026 Tacoma Product Information



Headroom (FR/RR)	39.7 in.* ¹ /38.4 in. or 38.0 in.* ² /38.4 in.
Legroom (FR/RR)	41.8 in./33.7 in.
Shoulder Room (FR/RR)	58.3 in./57.8 in.
Hip Room (FR/RR)	56.8 in./56.3 in.
Note	*1: Normal Roof *2: Moon Roof
WEIGHTS AND CAPACITIES (4x4 Double Cab)	
Curb weight (lbs.)	4,485-4,720
GVWR (lbs.)	5,865-6,305
Max Payload (lbs.)	1,380-1,705
Max Towing (lbs.)**	6,400
Max Tongue (lbs.)	640
Fuel Capacity	69 L
Engine Oil	5.3 L (with filter)
Cooling System	i-FORCE Engine: 12.1 L
Note	**Per SAE J2807 Methodology

AVAILABLE EXTERIOR COLOURS

- White
- Wind Chill Pearl*
- Celestial Silver Metallic
- Black
- Supersonic Red*
- Underground
- Bronze Oxide
- Mudbath
- Heritage Blue
- Wave Maker*
- White with Black Roof
- Underground with Black Roof

*Extra cost colour

BASIC LIMITED WARRANTY COVERAGE

- 3-year/60,000km Basic
- 5-year/100,000km Powertrain
- 8-year/160,000km Hybrid-Related Component Coverage
- 10-year/240,000km Hybrid Battery