



# TOYOTA

## 2026 Tundra i-FORCE MAX Product Information

ENGINE	
Type, Materials	i-FORCE: 3.5-liter aluminum block V6 hybrid, twin-turbochargers with water-cooled intercooler
Valve train	24-valve DOHC chain drive with Dual VVT-i
Displacement	3,445 cc
Bore x Stroke	85.5mm x 100mm
Compression Ratio	10.4:1
Horsepower	437 hp @ 5,200 rpm
Torque	583 lb-ft @ 2,400 rpm
Ignition System	DIS (Direct) with iridium-tipped spark plugs
Fuel System	D-4ST direct injection and port injection
Recommended Fuel	87-octane or higher
Emission Certification	LEV-III
Estimated Fuel Consumption (city/highway/combined)	12.7/11.5/11.7 L/100 km

ELECTRIC MOTOR (i-FORCE MAX)	
Type	Permanent Magnet Synchronous Motor
System	Parallel hybrid system with electric motor/generator located between engine and transmission
Electric Motor Power Output	48 hp (36 kw)
Torque	184 lb-ft (250 Nm)

HYBRID BATTERY PACK (i-FORCE MAX)	
Type	Sealed Nickel-Metal Hydride (Ni-MH) battery
Rated Voltage	288V (240 cells – 40 modules) Ex: 259.0 V (70 cells, 3.7V/cells)
Capacity	1.87 kWh
System Voltage	650 volts max

DRIVETRAIN	
Layout	4x4 front engine with on-demand part-time 4WD with electronically controlled two speed transfer case (high/low range) and Automatic Limited Slip Differential (Auto LSD) with Parallel hybrid system with electric motor/generator located between engine and transmission
Transmission Type	10-speed Electronically Controlled Automatic Transmission with intelligence (ECT[-i]), sequential shift mode, uphill/downhill shift logic, and TOW/HAUL driving modes



# TOYOTA

## 2026 Tundra i-FORCE MAX

### Product Information

Gear ratios	
1 <sup>st</sup>	4.92
2 <sup>nd</sup>	3.26
3 <sup>rd</sup>	2.35
4 <sup>th</sup>	1.94
5 <sup>th</sup>	1.53
6 <sup>th</sup>	1.19
7 <sup>th</sup>	1.00
8 <sup>th</sup>	0.80
9 <sup>th</sup>	0.66
10 <sup>th</sup>	0.61
Reverse	4.30
Differential ratio	3.31

TRANSFER CASE	
All models (high/low)	1.000/2.640

CHASSIS AND BODY		
Suspension	Front	Standard: Independent double-wishbone front suspension; coil spring multi-link rear suspension TRD Sport: TRD sport-tuned and lowered suspension with Bilstein® * shocks TRD Off-Road: TRD off-road suspension with Bilstein® * shocks TRD PRO: TRD Pro off-road suspension with 1.1-in. front lift, 2.5-in. FOX® * Internal Bypass coil-overs and rear remote-reservoir shocks, and TRD Pro front stabilizer bar
	Rear	Standard: Multi-link rear suspension with outboard-mounted coil springs - Available Adaptive Variable Suspension (AVS) - Load-leveling Rear Height Control Air Suspension
Steering	Type	Electronic Power Steering (EPS); power-assisted rack-and-pinion
	Turning Radius m(ft.)	7.4 (24.3)/7.9 (26) (Double Cab short/long) 7.4 (24.3)/7.62 (25) (CrewMax short/long)
	Turns (lock to lock)	3.4 (3.2 TRD Pro)
	Turning Circle Diameter (curb to curb) m (ft.)	14.8 (48.6)/15.85 (52) (Double Cab short/long) 14.8 (48.6)/15.24 (50) (CrewMax short/long) 15.18 (49.8) (TRD Pro)
Brakes	Front	Power-assisted ventilated 353 mm (13.9-in.) front disc brakes with opposed dual-piston calipers



# TOYOTA

## 2026 Tundra i-FORCE MAX

### Product Information

	Rear	Ventilated 345 mm (13.6-in.) rear disc brakes with single piston calipers
	Parking Brake	Electric Parking Brake (EPB)

STANDARD WHEEL TYPE, MATERIAL AND TIRE SIZE	
TRD OFF-ROAD	18-in. Off-Road Alloy Wheels with 265/70R18 tires
LIMITED	Limited TRD Off Road: 20-in. TRD Off-Road Matte Black Alloy Wheels with 265/60R20 tires Limited Nightshade: 20-in. TRD Sport Alloy Wheels with 265/60R20 tires
PLATINUM	20-in. Machine-finished Alloy Wheels with 265/60R20 tires
CAPSTONE	22-in. Alloy Wheels with 265/50R22 tires
1794	20-in. Machine-finished Alloy Wheels with 265/60R20 tires
TRD PRO	18-in. Black Forged aluminum BBS wheels with 285/65R18 all-terrain tires

EXT. DIMENSIONS	4x4 CrewMax	4x4 CrewMax Long Bed
Wheelbase mm (in.)	3700 (145.7)	4005 (157.7)
Overall Length mm (in.)	5932 (233.5)	6237 (245.5)
Overall Width (Max.) mm (in.)	2031 (80.0)	2031 (80.0)
Overall Height (Max.) mm (in.)	1984 (78.1)	1984 (78.1)
Inside Bed Length mm (in.)	1677 (66.0)	1982 (78.0)
Inside Bed Depth (in.)	20.9	20.9
Tread Front mm (in.)	1733 (68.2) Limited, Limited Longbox 1730 (68.1) TRD Pro. TRD Off Road, Capstone 1738 (68.4) Platinum	
Tread Rear mm (in.)	1735 (68.3) all except Platinum 1745 (68.7) Platinum	
Ground Clearance (mm/in.) i-FORCE Powertrain	282 (11.1) Limited, TRD Off Road, TRD PRO 279 (11.0) Limited Long Bed, TRD Off Road Long Bed, Platinum 277 (10.9) Capstone	
Coefficient of Drag	0.36	
Angle of Approach / Departure	21.0/24.0 (All models except TRD Pro) 26.2/24.2 (TRD Pro)	

Int. Dimensions	CrewMax
Seating Capacity	5
Headroom (Front/Rear)	1042 mm (41.0 in.) / 978 mm (38.5 in.) 998 mm (39.3 in.) / 937 mm (36.9 in.) (w/Panoramic Roof)
Legroom (Front/Rear)	1046.5 mm (41.2 in.) / 1056.6 mm (41.6 in.)
Shoulder Room (Front/Rear)	1651 mm (65.0in.) / 1585 mm (62.4 in.)
Hip Room (Front/Rear)	1590 mm (62.6 in.) 1537mm (60.5 in.)



# TOYOTA

## 2026 Tundra i-FORCE MAX

### Product Information

WEIGHTS AND CAPACITIES		4x4 CrewMax
Curb Weight	kg (lbs.)	2,725 (6007): Limited, TRD Off Road 2,765 (6096): Limited Long Bed, TRD Off Road Long Bed, Platinum, TRD PRO 2,805 (6184): Capstone
Towing Capacity kg (lbs.)	Regular bed:	5,067 (11,171): Limited, TRD Off Road 5,005 (11,034): Limited Long Bed, TRD Off Road Long Bed 4,995 (11,012): Platinum 4,690 (10,340): Capstone
GVWR	kg(lbs.)	3,455 (7,617): Limited, TRD Off Road 3,515 (7,749): Limited Long Bed, TRD Off Road Long Bed 3,475 (7,661): Platinum, TRD PRO 3,480 (7,672): Capstone
PAYLOAD	kg(lbs.)	730 (1,609): Limited, TRD Off Road 750 (1,653): Limited Long Bed, TRD Off Road Long Bed 710 (1,565): Platinum, TRD PRO 675 (1,488): Capstone
Fuel Capacity	L	122 L

Colours
<ul style="list-style-type: none"> <li>• White</li> <li>• Wind Chill Pearl*</li> <li>• Mudbath</li> <li>• Wavemaker</li> <li>• Lunar Rock</li> <li>• Blueprint</li> <li>• Supersonic Red*</li> <li>• Magnetic Grey Metallic</li> <li>• Celestial Silver Metallic</li> <li>• Midnight Black Metallic</li> </ul>

\*Extra cost colour

Basic Limited Warranty Coverage
<ul style="list-style-type: none"> <li>• 3-year/60,000km Basic</li> </ul>
<ul style="list-style-type: none"> <li>• 5-year/100,000km Powertrain</li> </ul>
<ul style="list-style-type: none"> <li>• 8-year/160,000km Hybrid-Related Component Coverage</li> </ul>
<ul style="list-style-type: none"> <li>• 10-year/240,000km Hybrid Battery</li> </ul>