



# TOYOTA

## 2026 Tundra i-FORCE Product Information

ENGINE	
Type, Materials	i-FORCE: 3.5-liter aluminum block V6, twin-turbochargers with water-cooled intercooler
Valve train	24-valve DOHC chain drive with Dual VVT-i
Displacement	3,445 cc
Bore x Stroke	85.5mm x 100mm
Compression Ratio	10.4:1
Horsepower	389 hp @ 5,200 rpm (SR: 358 hp @ 2,400)
Torque	479 lb-ft @ 2,400 rpm (SR: 406 lb-ft @ 2,000)
Ignition System	DIS (Direct) with iridium-tipped spark plugs
Fuel System	D-4ST direct injection and port injection
Recommended Fuel	87-octane or higher
Emission Certification	LEV-III
Estimated Fuel Consumption (city/highway/combined)	4x2 i-FORCE: 13.7/10.8/12.4 4x4 i-FORCE: 13.5/10.6/12.2

DRIVETRAIN	
Layout	4x2 front engine with rear-wheel drive with Automatic Limited-Slip Differential (Auto LSD) 4x4 front engine with on-demand part-time 4WD with electronically controlled two speed transfer case (high/low range) and Automatic Limited Slip Differential (Auto LSD)
Transmission Type	10-speed Electronically Controlled Automatic Transmission with intelligence (ECT[-i]), sequential shift mode, uphill/downhill shift logic, and TOW/HAUL driving modes
Gear ratios	
1 <sup>st</sup>	4.92
2 <sup>nd</sup>	3.26
3 <sup>rd</sup>	2.35
4 <sup>th</sup>	1.94
5 <sup>th</sup>	1.53
6 <sup>th</sup>	1.19
7 <sup>th</sup>	1.00
8 <sup>th</sup>	0.80
9 <sup>th</sup>	0.66
10 <sup>th</sup>	0.61
Reverse	4.30
Differential ratio	3.31



# TOYOTA

## 2026 Tundra i-FORCE Product Information

TRANSFER CASE	
All models (high/low)	1.000/2.640

CHASSIS AND BODY		
Suspension	Front	Standard: Independent double-wishbone front suspension; coil spring multi-link rear suspension TRD Sport: TRD sport-tuned and lowered suspension with Bilstein® * shocks TRD Off-Road: TRD off-road suspension with Bilstein® * shocks
	Rear	Standard: Multi-link rear suspension with outboard-mounted coil springs - Available Adaptive Variable Suspension (AVS) - Load-leveling Rear Height Control Air Suspension
Steering	Type	Electronic Power Steering (EPS); power-assisted rack-and-pinion
	Turning Radius m(ft.)	7.4 (24.3)/7.9 (26) (Double Cab short/long) 7.4 (24.3)/7.62 (25) (CrewMax short/long)
	Turns (lock to lock)	3.4
	Turning Circle Diameter (curb to curb) m (ft.)	14.8 (48.6)/15.85 (52) (Double Cab short/long) 14.8 (48.6)/15.24 (50) (CrewMax short/long)
Brakes	Front	Power-assisted ventilated 353 mm (13.9-in.) front disc brakes with opposed dual-piston calipers
	Rear	Ventilated 345 mm (13.6-in.) rear disc brakes with single piston calipers
	Parking Brake	Electric Parking Brake (EPB)

STANDARD WHEEL TYPE, MATERIAL AND TIRE SIZE	
SR	18-in. styled-steel wheels with 245/75R18 tires
SR5	18-in. alloy wheels with 265/70R18 tires
TRD OFF-ROAD	18-in. Off-Road Alloy Wheels with 265/70R18 tires
LIMITED	Limited TRD Off Road: 20-in. TRD Off-Road Matte Black Alloy Wheels with 265/60R20 tires
	Limited Nightshade: 20-in. TRD Sport Alloy Wheels with 265/60R20 tires
PLATINUM	20-in. Alloy Wheels with 265/60R20 tires
1794	20-in. Machine-finished Alloy Wheels with 265/60R20 tires



# TOYOTA

## 2026 Tundra i-FORCE Product Information

Ext. Dimensions	4x2 Double Cab	4x4 Double Cab	4x4 CrewMax
Wheelbase (Short bed/Long Bed)	3700 mm (145.7 in.) / 4180 mm (164.6 in.)	3700 mm (145.7 in.) / 4180 mm (164.6 in.)	3700(145.7) / 4005 mm (157.7)
Overall Length (Short bed/Long Bed)	5932 mm (233.5 in.)/ 6412 mm (252.4 in.)	5932 mm (233.5 in.)/ 6412 mm (252.4 in.)	5932 mm (233.5 in.) / 6237 mm (245.5 in.)
Overall Width (Max.)	2031 mm (80 in.)	2031 mm (80 in.)	2031 mm (80 in.)
Overall Height (Max. possible height)	1926 mm (75.8 in.)	2043 mm (80.4 in.)	2043 mm (80.4 in.)
Inside Bed Length	77.6 in. / 96.5 in.	77.6 in. / 96.5 in.	65.6 in. / 77.6 in.
Inside Bed Depth	530 mm/20.9 in.	530 mm/20.9 in.	530 mm/20.9 in.
Inside Bed Width (in.) - Total - Between Wheel Wells	1491 mm (58.7 in.) 1237mm (48.7 in.)	1491 mm (58.7 in.) 1237mm (48.7 in.)	1491 mm (58.7 in.) 1237mm (48.7 in.)
Track (Front/Rear)	1727 mm (68.in.) / 1735 mm (68.3 in.)	SR: 1729 38 mm (68.4 in.) / 1738 mm (68.4 in.) SR5, Off Road, Limited Off Road: 1730mm (68.1 in.)/ 1735mm (68.3 in.) SR5 Long Bed: 1730 mm (68.1 in.)/ 1738mm (68.4 in.)	Limited TRD Off Road: 1730 mm (68.1 in.)/ 1738mm (68.4 in.)  All other 4X4 Crewmax: 1738mm (68.4 in.)/ 1738mm (68.4 in.)
Ground Clearance (mm/in.) i-FORCE Powertrain	SR: 264mm (10.4 in.) Long bed: 262mm (10.3 in.)	SR, SR5, TRD Off-Road, TRD Sport: 279 mm/11.0 in. Limited: 277 mm /10.9 in. SR5 Long Bed: 274 mm/10.8 in.	<b>Regular bed:</b> SR5, TRD Off Road, TRD Sport, Limited: 279(11.0) Platinum, 1794: 277 (10.9) <b>Long bed:</b> SR, SR5, TRD Off Road, TRD Sport, Limited: 277(10.9) Platinum, 1794: 274(10.8)
Coefficient of Drag	0.36	0.36	0.36
Angle of Approach / Departure	23.0/22.9	18" wheel: 23.0/22.9 20" wheel: 22.9/22.0	18" wheel: 23.0/22.9 20" wheel: 22.9/22.0



**TOYOTA**

**2026 Tundra i-FORCE  
Product Information**

Int. Dimensions	Double Cab	CrewMax
Seating Capacity	5	5
Headroom (Front/Rear)	1042 mm (41.0 in.)/ 978 mm (38.5 in.) 998 mm (39.3 in.)/ 937 mm (36.9 in.) (w/Moonroof)	1042 mm (41.0 in.)/ 978 mm (38.5 in.) 998 mm (39.3 in.)/937 mm (36.9 in.) (w/Panoramic Roof)
Legroom (Front/Rear)	1046.5 mm (41.2 in.) 845.8 mm (33.3 in.)	1046.5 mm (41.2 in.) 1056.6 mm (41.6 in.)
Shoulder Room (Front/Rear)	1651 mm (65.0 in.) 1610.4mm (63.4 in.)	1651 mm (65.0in.) 1585 mm (62.4 in.)
Hip Room (Front/Rear)	1590 mm (62.6 in.) 1537mm (60.5 in.)	1590 mm (62.6 in.) 1537mm (60.5 in.)

WEIGHTS AND CAPACITIES		4x2 Double Cab	4x4 Double Cab	4x4 CrewMax
Curb Weight kg(lbs.)	Regular bed:	2310 (5092.7)	SR, SR5, TRD Off Road: 2440 (5379.3) Limited: 2490 (5489.5)	SR, SR5, TRD Off Road: 2445.00(5390.3) Limited: 2490.00(5489.5) Platinum, 1794: 2550.01(5621.8)
	Long bed:	2400 (5291.1)	2525 (5566.7)	SR5, TRD Off road: 2550.01(5621.8) Limited: 2595.01(5721.0) Platinum, 1794: 2630.02(5798.2)
Towing Capacity kg(lbs.)	Regular bed:	3760 (8289) SR	3760 (8289) (SR) 5080 (11199) (SR5, TRD Off Road) 5035 (11100) Limited, Limited TRD Off Road	5060 (11155) (SR5, TRD Off Road) 5045 (11122) (Limited) 5010 (11045) Platinum, 1794
	Long bed:	3760 (8289) SR	5030 (11089) SR5	4990 (11001) (SR5, TRD Off Road) 4975 (10968) (Limited) 4935 (10880) Platinum, 1794



# TOYOTA

## 2026 Tundra i-FORCE Product Information

GVWR	kg(lbs.)	3191.03 (7035) - 3249.99 (7165)	3295.35 (7265) - 3345.25 (7375)	3270.40 (7210) - 3340.71 (7365)
PAYLOAD	kg(lbs.)	850 (1874)- 880 (1940)	820 (1808)- 855 (1885)	715 (1576) - 790 (1742)
Fuel Capacity	L	122 L	122 L	122 L

### Colours

- White
- Wind Chill Pearl\*
- Lunar Rock
- Blueprint
- Supersonic Red\*
- Mudbath
- Magnetic Grey Metallic
- Celestial Silver Metallic
- Midnight Black Metallic

\*Extra cost colour

### Basic Limited Warranty Coverage

- 3-year/60,000km Basic
- 5-year/100,000km Powertrain